
Ecophon®
ACOUSTIC CEILINGS




Δ=20mm
The system is non-demountable


Ecophon Focus F

600x600, 1200x600


M15



1. Connect Direct fi xing plate F, installed at 600 mm centres (for use in concrete)




2. Connect Anchor screw, installed at 600 mm centres (for use in concrete)



3. Connect Installation screw MVL (for use in plasterboard or timber)




4. Connect Spline F, L=600 mm. Must be used in Sweden, Denmark, Norway and Finland at fireclass "Tändskyddande beklädnad"




5. Connect Spline, L=150 mm



6. Connect Wall spring spacer




7. Connect Angle trim, fixed at 300 mm centres



8. Timber installed at 600 mm centres (300 mm if thermal insulation is placed above), with the screw fi xings along the timber.

9. For use when installing floatingceilings: Connect Wood trim, L=2500 mm, fixedat500 mm centres





Installation guide IG15

Art.no 9010641
2008.10

Ecophon®
www.ecophon.com

1






2

19


2





3


4

4













3







3¹







22
22
c300
22
22
Connect
Installation screw
MWL, PH2

4



600x600
300-600
300-600
?
300-600
300-600
?


5


1200x600




5[1]











6 6 13





6




7


Connect Installation
screw MVL
600x600:3x
1200x600:5x
PH2



Connect
Spline 0219
Connect
Spline F
8
1
2
3
4



9
1
2
3
4
5
6




10













Connect Wall spring
spacer 0087
600x600 x1
1200x600 x2








11











12
18
19
20
21
22
9
10
11
12
1
2
3
4
24
5
6
7
8
23
13
14
15
16
17
1
2
3



Connect Direct
fixing plate F0149
Connect
Installation screw
F4000
13
1
≥ 40
10
Ø4
T20



14
1
2
3
4







15











16








x
x+7
17
14
16
18
20
22
13
15
17
19
1
2
3
4
5
7
11
6
8
12
21
1
2
3



18
14
16
18
20
22
13
15
17
19
1
2
3
4
24
5
7
9
11
23
6
8
10
12
21
1
2
3








19













6-10


13-16

20





21



22

